

CNCEN Industrial Cooler

Item		ZCC-203A	ZCC-305A	ZCC-308A	ZCC-510A	ZCC-715A	ZCC-1020A	ZCC-1525A	ZCC-1530A
Air Cooling Temperature 冷风温度	°C					8~15			
Cooling Capacity 制冷量	Kcal/H-50Hz	6900	11280	18900	25200	37800	50400	63000	75600
	Kcal/H-60Hz	8200	13260	22680	32240	45360	60480	75600	90720
Power 电源	V				3 φ380V50HZ				
Rated Power 输入功率	Kw	2.4	3.9	6.8	8.6	13	17.3	22	25.5
Cooling Fan 冷却风机	KW	0.18x1	0.25x2	0.25x2	0.25x2	0.55x2	0.55x2	0.25x4	0.55x3
Cooling Fan Capacity 冷却风量	m3/min	18	28	38	48	58	68	78	88
Air Outlet Port 出风管径	In	3		4		8		10	
Refrigerant 冷媒	R				R22、R407C				
Temperature Control 温控			LCD temperature display micro-computer temperature control 液晶温度显示,微电脑温度控制						
Size (L x W x H) 外型尺寸	MM	1100x800x1480	1370x800x1600	1670 x 880 x 1850		2210 x 1060 x 1950		2620 x 1120 x 1950	
Weight 机器重量	KG	270	350	420	530	620	820	880	980
Protection Device 保护装置		入风口过滤网、高压保护、低压保护、缺相保护、冷媒不足保护、散热不良保护、马达过载保护、主机过载、水泵过载、IC故障警报回路 Air inlet filter, High pressure protection, Low pressure protection, Phase-lacking protection, Insufficient refrigerant protection, Poor heat dissipation protection, Motor overload protection, Compressor overload protection, Pump overload protection, IC trouble warning.							

Note : Refrigerating capacity is based on condition of 35°C (D.B), 24°C(W.B) ; inlet condensation water temperature at 32°C, outlet condensation water temperature at 37°C; inlet chilled water temperature at 12°C, outlet chilled water temperature at 7°C.
We reserve the right to modify the above information without further notice.